



BEAVER¹⁸ FIREWOOD PROCESSOR

New
The Workhorse of the Family!



The Model 18 is quickly becoming our most popular machine – a real work horse (or rather, beaver!). Capable of doing 2 + cords per hour with good size wood, it's fast and efficient. With our proprietary Super Split regenerative hydraulic system the splitter cycles at an incredible 4-4.5 seconds! The live in feed and 8' discharge conveyor are standard on the 18 – choose a log lift, dead deck or live deck for loading and you have a full on production machine that will keep the wood pile ready. Equipped with either PTO or engine driven tandem 10 gpm pumps and with our exclusive serial hydraulic valve system the 18 thinks nothing of multi-tasking. Go ahead, run the saw and splitter together – it not only won't flinch, it won't even slow down. For engines, choose from the standard Honda GX630, or optional Honda GX690 or Kohler ECH 749 EFI, or even a Kubota 902 or Kohler 1003 diesel. The optional highway package makes it easy to move around the woodlot or down the road. This machine is THE firewood factory!

MODEL 18

Maximum Performance & Value at a Minimum Price

Performance:

2 plus full cords per hour (128 Cubic feet per cord)
Cuts up to 17+” diameter wood
Splits wood from 3” to 24” in length
“Super Splitter” cycle time **Super Fast** 4 to 4.5 seconds
Honda engine GX 630 (optional engines below)
Hydraulic saw 20” harvester bar and 3/8” chain
Integral bar oil reservoir in chain guard
Extended live infeed standard - mill grade belt for positive infeed & durability
Single axle 4400# with lights and brakes, highway pkg.
8’ stacking conveyor – optional 12’
Protective lockout cover – splitting & cutting
Log “cam” length measure system – moves to relieve cut
2/4 way/optional 6 way wedge quick interchange system
Manual saw bar and wedge adjustment-optional “EASY” controls- Hydraulic saw-raise & lower and Hydraulic wedge controls (additional cost)

Options:

2~Strand dead deck attached
2-Strand hydraulic live deck attached with manual winch
Log Lift/Hydraulic, attaches to unit with 3’ extension on live in feed
Hydraulic Raise lower on wedge
Conveyor extension extra 48” with manual winch
6 Way wedge
Engine – Honda GX 690, Kohler ECH749 EFI, or Kohler 1003 or Kubota 902 Diesel
Operator’s Seat



Specifications:

Transport width - 5'
Transport length - 19'
Trailer hitch – 2” ball
Hydraulic capacity – 22 US Gallons

Operation width – 5'
Weight – 3850 lbs. (approx.)
Transport height – 9’6”